

MAJILITE CUSTOM

Coated Fabrics & Specialized Films

Lansdorf 1001 Medical Film Technical Data Sheet

Product Description

Lansdorf 1001 Film is a thin cast aliphatic polyester urethane film possessing resistance to degradation by moisture. It also has uniform thickness with a matte finish, excellent elongation, and low modulus.

Features and Benefits

- Lansdorf 1001 has low coefficient-of-friction, a very smooth feel and no tack
- This film displays high elongation, with low modulus
- Matte finish enhances low slip characteristics
- Urethane allows moisture vapor and other gases to pass through
- Clear film you can see through
- Good stretch and recovery with resistance to high temperatures
- Casting process produces a uniform thickness with no gel particles or unseen film orientation
- Lansdorf 1001 is Mineral Oil resistant

Typical Physical Properties (1.0 mil thickness)

Standard Color	Clear
Elongation at Break	550%
100% Modulus	2.5 Newtons
Moisture Vapor Trans**	1100 gms/m ² /24hr
Liner	60 lb coated bleached kraft

**ASTM E-96 @ 50% RH with upright cups.

Availability

Lansdorf 1001	Film is available from thickness of 0.6 mils to 3+ mils	
	<u>Log Roll</u>	<u>Slit Roll</u>
Width	58 inches	1 inch & wider
Std. Length	750 feet	750 feet
Core Size	3 inches	3 inches

Optional Considerations

- Film colors: white, flesh tint and others
- Additives to impart or alter specific properties

Product Safety

The components used in Lansdorf film are listed in Title 21 of the Code of Federal Regulations. In vitro cytotoxicity tests were conducted using MEM elution procedures. Good Manufacturing Practices and the Device Amendments of the Federal Food, Drug and Cosmetic Act place the burden of demonstrating product safety on the device manufacturer.

Majilite warrants that the products sold by it conform to its published specifications, if any, and that the products are merchantable. Test data contained herein pertaining to Majilite's products, or elsewhere published or provided to the customer by Majilite are believed to be reliable, but unless specifically stated, are not part of the specifications for the products. Majilite disclaims any warranty, express or implied, that products are fit for a particular purpose, and the customer is solely responsible for determining the suitability of Majilite's products for its intended use, regardless of any advice provided by Majilite. Majilite further disclaims any warranty related to the infringement or misappropriation of any third party's intellectual property rights related to the products or the use or sale thereof."