# MAJILITE CUSTOM

Coated Fabrics & Specialized Films

### Lansdorf 1001 Medical Film Technical Data Sheet

## Product Description

Lansdorf 1001 Film is a thin cast aliphatic polyester urethane film possessing resistance to degradation by moisture. It also has uniform thickness with a matte finish, excellent elongation, and low modulus.

#### Features and Benefits

- Lansdorf 1001has low coefficient-of-friction, a very smooth feel and no tack
- This film displays high elongation, with low modulus
- Matte finish enhances low slip characteristics
- Urethane allows moisture vapor and other gases to pass through
- · Clear film you can see through
- Good stretch and recovery with resistance to high temperatures
- Casting process produces a uniform thickness with no gel particles or unseen film orientation
- Lansdorf 1001 is Mineral Oil resistant

#### Typical Physical Properties (1.0 mil thickness)

Standard Color Clear
Elongation at Break 575%
100% Modulus 3.0 Newtons
Moisture Vapor Trans\*\* 1150 gms/m²/24hr

Liner 60 lb coated bleached kraft

#### Availability

Lansdorf 1001 Film is available from thickness of 0.6 mils to 3+ mils

Log Roll

Width 59 inches Std. Length 1,200 yards Core Size 3 inches

#### **Optional Considerations**

- Film colors: white, flesh tint and others
- Additives to impart or alter specific properties

#### **Product Safety**

The components used in Lansdorf film are listed in Title 21 of the Code of Federal Regulations. In vitro cytotoxicity tests were conducted using MEM elution procedures. Good Manufacturing Practices and the Device Amendments of the Federal Food, Drug and Cosmetic Act place the burden of demonstrating product safety on the device manufacturer. Majilite warrants that the products sold by it conform to its published specifications, if any, and that the products are merchantable. Test data contained herein pertaining to Majilite's products, or elsewhere published or provided to the customer by Majilite are believed to be reliable, but unless specifically stated, are not part of the specifications for the products. Majilite disclaims any warranty, express or implied, that products are fif for a particular purpose, and the customer is solely responsible for determining the suitability of Majilite's products for its intended use, regardless of any advice provided by Majilite. Majilite further disclaims any warranty related to the infringement or misappropriation of any third party's intellectual property rights related to the products or the use or sale thereof."

<sup>\*\*</sup>ASTM E-96 @ 50% RH with upright cups.