

MAJILITE CUSTOM

Coated Fabrics & Specialized Films

Lansdorf 1200 Medical Film Technical Data Sheet

Product Description

Lansdorf 1200 is a thin cast aromatic polycarbonate urethane film possessing excellent resistance to degradation by moisture. It also has uniform thickness with a matte finish, excellent elongation, strength and conformability.

Features and Benefits

- Matte finish gives low slip characteristics
- Urethane allows moisture vapor and other gases to pass through
- Casting process produces a uniform thickness with no gel particles or unseen film orientation, and a clear film you can see through
- Lansdorf 1200 is Mineral Oil resistant
- The film is lightweight with low bulk, flexible and conformable
- Lansdorf 1200 displays excellent resistance to hydrophilic degradation

Typical Analytical Values (1.0 mil thickness)

Standard Color	Clear
Elongation at Break	390%
100% Modulus	5.9 Newtons
Moisture Vapor Trans**	860 gms/m ² /24hr
Liner	60 lb coated kraft

**ASTM E-96 @ 50% RH with upright cups.

Availability

Lansdorf 1200	Film is available from thickness of 0.6 mils to 3+ mils
	<u>Log Roll</u>
Width	59 inches
Std. Length	1,200 yards
Core Size	3 inches

Optional Considerations

- Film colors: white, flesh tint and others
- Liners with different basis weights
- Additives to impart or alter specific properties

Product Safety

The components used in Lansdorf film are listed in Title 21 of the Code of Federal Regulations. In vitro cytotoxicity tests were conducted using MEM elution procedures. Good Manufacturing Practices and the Device Amendments of the Federal Food, Drug and Cosmetic Act place the burden of demonstrating product safety on the device manufacturer. Majilite warrants that the products sold by it conform to its published specifications, if any, and that the products are merchantable. Test data contained herein pertaining to Majilite's products, or elsewhere published or provided to the customer by Majilite are believed to be reliable, but unless specifically stated, are not part of the specifications for the products. Majilite disclaims any warranty, express or implied, that products are fit for a particular purpose, and the customer is solely responsible for determining the suitability of Majilite's products for its intended use, regardless of any advice provided by Majilite. Majilite further disclaims any warranty related to the infringement or misappropriation of any third party's intellectual property rights related to the products or the use or sale thereof.